



Concrete Flex - Care and Maintenance Instructions

Concrete Flex should be treated like a standard stone or concrete product, which means it is recommended to apply a 'sealer' to protect the material from topical stains. This sealer coating will provide surface protection that aids in stain resistance and the clean ability of the product. For specific recommendations, please inquire.

Generally speaking, stains should be removed from any wall or applied surface as quickly as possible to eliminate any possible reaction between the staining agent and the product. Time is especially important for removing materials containing colors or solvents such as ball point pens, nail polish, lipstick, oil shampoo tints, paint, lacquer, enamel, and certain food items.

Precautions: Excess soiling materials such as chewing gum, asphalt, crayon, paint, nail polish, or tar should be carefully scraped off prior to the application of other cleaning attempts.

Cleaning: The normal cleaning of the product should be done with a dry and soft lint-free cloth or dry sponge. If stained, a stronger cleaning is required. Rinse thoroughly with clean, clear water, often to insure the water remains clean and clear. After cleaning an area, be sure to dry with an absorbent cloth so it can be examined to ensure complete cleaning.

NOTE: NEVER USE ABRASIVE CLEANERS OR MIX CLEANING REAGENTS TOGETHER, AS VIOLENT REACTIONS MAY OCCUR WHEN CHEMICALS ARE MIXED WHICH COULD CAUSE VIOLENT REACTIONS. OBSERVE ALL LABEL PRECAUTIONS WHEN USING ANY CLEANING AGENTS.