

CORK BARK – Virgin Tree™



VIRGIN TREE

Tile Dimension	1480*600mm (58-1/4" x 23-5/8")
Tile Depth	25mm (1")
Coverage per tile	9.56 sq.ft.
Weight per tile	4 lbs.

Product Overview

The **CORK BARK – Virgin Tree™** are large format cork panels that visually represent the outermost layer of the cork bark found on the Cork Oak tree. The texture is rough, pitted, and is a mix of brown and grey colors in the 'natural' version. The Virgin Tree panels take segments of this bark, which then get mounted onto a plywood substrate. The standard version of the Virgin Tree comes with embedded Reindeer moss strategically placed throughout the panel (note: a plain version, without moss, is also available).

OUTER BARK 



Specifications

Description: Large format cork bark panel that highlights the natural mottled and rough texture found naturally in the outer bark of the cork oak trees.

Color (select one): Natural, Ivory, Green, Brown, Terracota, Sandstone Black

Composition: 100% recycled cork

Fire-rating: Class "C" (Note: considered Class "B" in 'sprinkled' assemblies)


NRC: not tested (assumed to be approx. 0.15)

Installation: Direct applied with Wakol Loba MS262 (construction adhesive) or D3540 (water-based contact cement)


Colors




Natural




Ivory




Brown



Terracota



Green



Sandstone Blk

Sustainable Attributes

- Made from rapidly renewable cork (harvested without harm to tree on 9-year cycle)
- Recycled content:
 - made from 100% industrial by-product cork
- Carbon neutral product
- Zero-carbon manufacturing
- Low-VOC and CDPH compliant
- High-touch handmade product
- Sustainable supply chain and anti-modern slavery

Environmental Certification

- HPD (Health Product Declaration) – Portico:2016
- Fire Test compliance – ASTM E84-15a
- VOC compliance – EN ISO/IEC 17025

Installation adhesive certifications (with recommended: Wakol Loba D3540)

- Floor Score certification
- EC1 Certification
- Bay Area Air District compliance (BBAQMD – Regulation 8, Rule 51)
- South Coast Air Quality Management District compliance (SCAQMD– Rule 1168)

Green Building Certification

Sustainable Materials products meet criteria for WELL, LEED, Green Star, and BREEAM building rating systems, helping you achieve certification for your project. For support and guidance on available rating system points please visit www.SustainableMaterials.com, or speak with your Sustainable Materials account manager.

Product Testing Specifications

Fire-rating: Class C (per ASTM – E84); (Note: in 'sprinkled' assemblies, per NFPA 2015, these equate to a Class "B").

Thermal Conductivity: 0.0541 W/mC

Dimensional Stability: ≤ 0.4 % (per EN 434)

Sound Absorption: Not tested, but assumed to achieve an NRC = ~0.15

Thermal Resistance: 0.46 m²C/W

Pattern repeat: No pattern repeat (non-woven).